

- High Capacitive Drive Capability
- 'ALS1808A Has Typical Delay Time of 4.8 ns ($C_L = 50 \text{ pF}$) and Typical Power Dissipation of 4.5 mW per Gate
- 'AS1808 Has Typical Delay Time of 3.2 ns ($C_L = 50 \text{ pF}$) and Typical Power Dissipation of Less than 13 mW per Gate
- Center V_{CC} and GND Configuration Provides Minimum Lead Inductance in High Current Switching Applications
- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

description

These devices contain six independent 2-input AND drivers. They perform the Boolean functions $Y = A \cdot B$ or $Y = \bar{A} + \bar{B}$ in positive logic.


The center pin configuration used in the 'ALS1808A and 'AS1808 provides a reduction of lead inductance when compared to the 'ALS808A and 'AS808B. This reduction of lead inductance will minimize noise generated onto either the V_{CC} or GND bus. This reduction is significant in high current switching applications.

The SN54ALS1808A and SN54AS1808 are characterized for operation over the full military temperature range of -55°C to 125°C . The SN74ALS1808A and SN74AS1808 are characterized for operation from 0°C to 70°C .

FUNCTION TABLE (each driver)


INPUTS		OUTPUT
A	B	Y
H	H	H
L	X	L
X	L	L

SN54ALS1808A, SN54AS1808 . . . J PACKAGE
SN74ALS1808A, SN74AS1805 . . . N PACKAGE
(TOP VIEW)




Use 'ALS808A or 'AS808B for chip carrier option.

logic symbol†



†This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

logic diagram (positive logic)



SN54ALS1808A, SN75ALS1808A HEX 2-INPUT AND DRIVERS

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V _{CC}	7 V
Input voltage	7 V
Operating free-air temperature range: SN54ALS1808A	-55°C to 125°C
SN74ALS1808A	0°C to 70°C
Storage temperature range	-65°C to 150°C

recommended operating conditions

2

ALS and AS Circuits

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54ALS1808A			SN74ALS1808A			UNIT
		MIN	TYP [†]	MAX	MIN	TYP [†]	MAX	
V _{IK}	V _{CC} = 4.5 V, I _I = -18 mA			-1.2			-1.2	V
	V _{CC} = 4.5 V to 5.5 V, I _I = -0.4 mA	V _{CC} - 2			V _{CC} - 2			
V _{OH}	V _{CC} = 4.5 V, I _{OH} = -3 mA	2.4	3.2		2.4	3.2		V
	V _{CC} = 4.5 V, I _{OH} = -12 mA	2						
V _{OL}	V _{CC} = 4.5 V, I _{OL} = 12 mA	0.25	0.4		0.25	0.4		V
	V _{CC} = 4.5 V, I _{OL} = 24 mA				0.35	0.5		
I _I	V _{CC} = 5.5 V, V _I = 7 V			0.1			0.1	mA
I _{IH}	V _{CC} = 5.5 V, V _I = 2.7 V			20			20	μA
I _{IL}	V _{CC} = 5.5 V, V _I = 0.4 V			-0.1			-0.1	mA
I _O [‡]	V _{CC} = 5.5 V, V _O = 2.25 V	-30		-112	-30		-112	mA
I _{CCH}	V _{CC} = 5.5 V, V _I = 4.5 V		4.5	7	4.5	7		mA
I _{CCL}	V _{CC} = 5.5 V, V _I = 0 V		8	16	8	16		mA

[†]All typical values are at V_{CC} = 5 V, T_A = 25°C.

[‡]The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS}.

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 5 V, C _L = 50 pF, R _L = 500 Ω, T _A = 25°C	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 500 Ω T _A = MIN to MAX				UNIT		
			'ALS1808A		SN54ALS1808A		SN74ALS1808A			
			TYP	MIN	MAX	MIN	MAX			
t _{PLH}	A or B	Y		6	2	11	2	9	ns	
t _{PHL}				4	1	10	1	8		

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V _{CC}	7 V
Input voltage	7 V
Operating free-air temperature range: SN54AS1808	-55°C to 125°C
SN74AS1808	0°C to 70°C
Storage temperature range	-65°C to 150°C

recommended operating conditions

		SN54AS1808			SN74AS1808			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V _{IH}	High-level input voltage	2			2			V
V _{IL}	Low-level input voltage				0.8		0.8	V
I _{OH}	High-level output current				-40		-48	mA
I _{OL}	Low-level output current				40		48	mA
T _A	Operating free-air temperature	-55	125	0	0	70	°C	

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS		SN54AS1808			SN74AS1808			UNIT
	MIN	TYP†	MAX	MIN	TYP†	MAX			
V _{IK}	V _{CC} = 4.5 V,	I _I = -18 mA		-1.2		-1.2			V
V _{OH}	V _{CC} = 4.5 V to 5.5 V,	I _{OH} = -2 mA	V _{CC} -2		V _{CC} -2				
	V _{CC} = 4.5 V,	I _{OH} = -3 mA	2.4	3.2	2.4	3.2			V
V _{OL}	V _{CC} = 4.5 V,	I _{OH} = -40 mA	2				2		V
	V _{CC} = 4.5 V,	I _{OH} = -48 mA							
I _{O‡}	V _{CC} = 4.5 V,	I _{OL} = 40 mA	0.25	0.5					V
	V _{CC} = 4.5 V,	I _{OL} = 48 mA					0.35	0.5	
I _I	V _{CC} = 5.5 V,	V _I = 7 V		0.1		0.1			mA
I _{IH}	V _{CC} = 5.5 V,	V _I = 2.7 V		20		20			µA
I _{IL}	V _{CC} = 5.5 V,	V _I = 0.4 V		-0.5		-0.5			mA
I _{O‡}	V _{CC} = 5.5 V,	V _O = 2.25 V	-50	-200	-50	-200			mA
I _{CCH}	V _{CC} = 5.5 V,	V _I = 4.5 V		8	13	8	13		mA
I _{CCL}	V _{CC} = 5.5 V,	V _I = 0 V		20	33	20	33		mA

†All typical values are at V_{CC} = 5 V, T_A = 25°C

‡The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS}.

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 500 Ω, T _A = MIN to MAX				UNIT	
			SN54AS1808		SN74AS1808			
			MIN	MAX	MIN	MAX		
t _{PLH}	A or B	Y	1	6.5	1	6	ns	
			1	6.5	1	6		

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.