

- High Capacitive Drive Capability
- 'ALS1805A Has Typical Delay Time of 4.2 ns ( $C_L = 50 \text{ pF}$ ) and Typical Power Dissipation of 4.2 mW per Gate
- 'AS1805 Has Typical Delay Time of 2.6 ns ( $C_L = 50 \text{ pF}$ ) and Typical Power Dissipation of Less than 12 mW per Gate
- Center  $V_{CC}$  and GND Configuration Provides Minimum Lead Inductance in High Current Switching Applications
- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

### description

These devices contain six independent 2-input NOR drivers. They perform the Boolean functions  $Y = A + B$  or  $Y = \overline{A} \cdot \overline{B}$  in positive logic.

The center pin configuration used in the 'ALS1805A and 'AS1805 provides a reduction of lead inductance when compared to the 'ALS805A and 'AS805B. This reduction of lead inductance will minimize noise generated onto either the  $V_{CC}$  or GND bus. This reduction is significant in high current switching applications.


The SN54ALS1805A and SN54AS1805 are characterized for operation over the full military temperature range of  $-55^\circ\text{C}$  to  $125^\circ\text{C}$ . The SN74ALS1805A and SN74AS1805 are characterized for operation from  $0^\circ\text{C}$  to  $70^\circ\text{C}$ .

FUNCTION TABLE (each driver)

INPUTS		OUTPUT
A	B	Y
H	X	L
X	H	L
L	L	H


SN54ALS1805A, SN54AS1805 . . . J PACKAGE  
SN74ALS1805A, SN74AS1805 . . . N PACKAGE

(TOP VIEW)




Use 'ALS805A or 'AS805B for chip carrier option.

### logic symbol†



†This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

### logic diagram (positive logic)



PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

## **SN54ALS1805A, SN74ALS1805A HEX 2-INPUT NOR DRIVERS**

**absolute maximum ratings over operating free-air temperature range (unless otherwise noted)**

Supply voltage, V <sub>CC</sub>	7 V
Input voltage	7 V
Operating free-air temperature range:	
SN54ALS1805A	-55 °C to 125 °C
SN74ALS1805A	0 °C to 70 °C
Storage temperature range	-65 °C to 150 °C

#### **recommended operating conditions**

		SN54ALS1805A			SN74ALS1805A			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V <sub>CC</sub>	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V <sub>IH</sub>	High-level input voltage		2			2		V
V <sub>IL</sub>	Low-level input voltage			0.7			0.8	V
I <sub>OH</sub>	High-level output current			-12			-15	mA
I <sub>OL</sub>	Low-level output current			12			24	mA
T <sub>A</sub>	Operating free-air temperature	-55		125	0		70	°C

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	SN54ALS1805A			SN74ALS1805A			UNIT
		MIN	TYP†	MAX	MIN	TYP†	MAX	
V <sub>IK</sub>	V <sub>CC</sub> = 4.5 V, I <sub>I</sub> = -18 mA	-	-1.2	-	-	-1.2	-	V
V <sub>OH</sub>	V <sub>CC</sub> = 4.5 V to 5.5 V, I <sub>OH</sub> = -0.4 mA	V <sub>CC</sub> -2	-	V <sub>CC</sub> -2	-	-	-	V
	V <sub>CC</sub> = 4.5 V, I <sub>OH</sub> = -3 mA	2.4	3.2	2.4	3.2	-	-	
	V <sub>CC</sub> = 4.5 V, I <sub>OH</sub> = -12 mA	2	-	-	-	-	-	
	V <sub>CC</sub> = 4.5 V, I <sub>OH</sub> = -15 mA	-	-	2	-	-	-	
	V <sub>CC</sub> = 4.5 V, I <sub>OL</sub> = 12 mA	0.25	0.4	0.25	0.4	-	-	
V <sub>OL</sub>	V <sub>CC</sub> = 4.5 V, I <sub>OL</sub> = 24 mA	-	-	0.35	0.5	-	-	V
	V <sub>CC</sub> = 4.5 V, I <sub>OL</sub> = 48 mA	-	-	-	-	-	-	
I <sub>I</sub>	V <sub>CC</sub> = 5.5 V, V <sub>I</sub> = 7 V	-	0.1	-	0.1	-	mA	
I <sub>IH</sub>	V <sub>CC</sub> = 5.5 V, V <sub>I</sub> = 2.7 V	-	20	-	20	-	μA	
I <sub>IL</sub>	V <sub>CC</sub> = 5.5 V, V <sub>I</sub> = 0.4 V	-	-0.1	-	-0.1	-	mA	
I <sub>O</sub> ‡	V <sub>CC</sub> = 5.5 V, V <sub>O</sub> = 2.25 V	-30	-112	-30	-112	-	mA	
I <sub>CCH</sub>	V <sub>CC</sub> = 5.5 V, V <sub>I</sub> = 0 V	2	4	2	4	-	mA	
I <sub>CCCL</sub>	V <sub>CC</sub> = 5.5 V, V <sub>I</sub> = 4.5 V	8	14	8	14	-	mA	

<sup>†</sup> All typical values are at  $V_{CC} = 5$  V,  $T_A = 25^\circ\text{C}$ .

<sup>‡</sup> The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current,  $I_{OS}$ .

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 5\text{ V}$ ,	$V_{CC} = 4.5\text{ V to }5.5\text{ V}$ ,		UNIT	
			$C_L = 50\text{ pF}$ ,	$C_L = 50\text{ pF}$ ,			
			$R_L = 500\Omega$ ,	$R_L = 500\Omega$ ,			
			$T_A = 25^\circ\text{C}$	$T_A = \text{MIN to MAX}$			
			'ALS1805A	SN54ALS1805A	SN74ALS1805A		
			TYP	MIN	MAX	MIN	MAX
tPLH	A or B	Y	4	2	9	2	7
tPHL			5	2	10	2	8

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

**absolute maximum ratings over operating free-air temperature range (unless otherwise noted)**

Supply voltage, V <sub>CC</sub>	7 V
Input voltage	7 V
Operating free-air temperature range:	
SN54AS1805	-55°C to 125°C
SN74AS1805	0°C to 70°C
Storage temperature range	-65°C to 150°C

#### **recommended operating conditions**

		SN54AS1805			SN74AS1805			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V <sub>CC</sub>	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V <sub>IH</sub>	High-level input voltage		2			2		V
V <sub>IL</sub>	Low-level input voltage			0.8			0.8	V
I <sub>OH</sub>	High-level output current			-40			-48	mA
I <sub>OL</sub>	Low-level output current			40			48	mA
T <sub>A</sub>	Operating free-air temperature	-55	125	0	0	70	70	°C

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)**

PARAMETER	TEST CONDITIONS			SN54AS1805			SN74AS1805			UNIT
		MIN	TYP†	MAX	MIN	TYP†	MAX			
V <sub>IK</sub>	V <sub>CC</sub> = 4.5 V, V <sub>CC</sub> = 4.5 V to 5.5 V, V <sub>CC</sub> = 4.5 V, V <sub>CC</sub> = 4.5 V, V <sub>CC</sub> = 4.5 V,	I <sub>I</sub> = -18 mA I <sub>OH</sub> = -2 mA I <sub>OH</sub> = -3 mA I <sub>OH</sub> = -40 mA I <sub>OH</sub> = -48 mA	-	-1.2	-	-1.2	-	V		
V <sub>OH</sub>		V <sub>CC</sub> = 2	V <sub>CC</sub> = 2		2.4	3.2	2.4	3.2	V	
V <sub>OL</sub>	V <sub>CC</sub> = 4.5 V, V <sub>CC</sub> = 4.5 V,	I <sub>OL</sub> = 40 mA I <sub>OL</sub> = 48 mA	0.25	0.5	0.35	0.5		V		
I <sub>I</sub>	V <sub>CC</sub> = 5.5 V,	V <sub>I</sub> = 7 V	0.1		0.1		mA			
I <sub>IH</sub>	V <sub>CC</sub> = 5.5 V,	V <sub>I</sub> = 2.7 V	20		20		μA			
I <sub>IL</sub>	V <sub>CC</sub> = 5.5 V,	V <sub>I</sub> = 0.4 V	-0.5		-0.5		mA			
I <sub>O‡</sub>	V <sub>CC</sub> = 5.5 V,	V <sub>O</sub> = 2.25 V	-50	-200	-50	-200	mA			
I <sub>CH</sub>	V <sub>CC</sub> = 5.5 V,	V <sub>I</sub> = 0 V	6.5	10	6.5	10	mA			
I <sub>CL</sub>	V <sub>CC</sub> = 5.5 V,	V <sub>I</sub> = 4.5 V	20	32	20	32	mA			

<sup>†</sup>All typical values are at  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

<sup>†</sup>All typical values are at  $V_{CC} = 5\text{ V}$ ,  $I_A = 29^\circ\text{C}$ .  
<sup>‡</sup>The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current,  $I_{OS}$ .

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V},$ $C_L = 50 \text{ pF},$ $R_L = 500 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT	
			SN54AS1805					
			MIN	MAX	MIN	MAX		
			1	4.8	1	4.3		
$t_{PLH}$	A or B	Y	1	4.8	1	4.3	ns	
$t_{PHL}$			1	4.8	1	4.3		

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.